



Bitulastic

Samson Bitulastic is a waterproofing elastomeric, bituminous liquid membrane suitable for various roof types.

Colour: Black

PRODUCT USES

- Corrugated and IBR galvanized roofs.
- Granular, smooth or asbestos/fibre cement profiled roof tiles

ADVANTAGES

- Excellent flexibility and adhesion
- Maximum coverage
- Water based
- Ease of application
- Non-flammable
- Weather resistant

THEORETICAL SPREAD RATE

- 2m² per litre based on a 2 coat application.
- This is a guide only and the practical spread rate depends on substrate porosity and profile as well as technique and tools used.

SURFACE PREPARATION

- Ensure all surfaces are thoroughly clean, dry and free from contaminations such as dust, oil and chemical contaminates.

APPLICATION

- Stir Samson Synlastic thoroughly prior to using a stirring tool attached to an electric drill.
- Apply undiluted using a block brush / soft broom or spray gun.
- Allow to dry for 3-4 hours (depending on climatic conditions)
- Apply second coat

CLEANING

- Soak brushes in water.
- Collect spills with suitable absorbent material.

IMPORTANT

- Do not apply if rain is expected.
- To ensure colour consistency check that the batch numbers are the same on all packaging.

SAFETY PRECAUTIONS

- Skin contact: Wash thoroughly with soap and water.
- Eye contact: Flush immediately with water and contact a physician.
- Respiratory problems: Remove affected person to fresh air immediately and contact a physician.
- Not for consumption. If swallowed, contact a doctor immediately. Do not induce vomiting. Drink water.
- Keep out of reach of children.
- Do not pour paint down the drain

TECHNICAL DATA

- Pack size 5 litre and 20litre buckets
- Touch dry 2 hours
- Hard dry 4 hours
- Over coating time 24 hours
- Full Cure 7 days
- Mass solids $\pm 60\%$
- Application temperature 10°C to 35°C
- Density 1.03g /l
- Toxicity Non Toxic
- Fire hazard None
- Shelf life 6-12 months (dependent on storage conditions)
- Storage Cool, dry area below 25°C

Properties listed above are for guidance only and not a guarantee on performance.

Technical details above are provided in good faith. We are an ISO 9001: 2008 registered company and our products are manufactured to the highest standards using raw materials of superior quality. Consequently we believe in the quality of our products and will willingly replace any product in the unlikely event of a quality related performance failure. Whilst we are confident in guaranteeing the quality of our products, we cannot however accept any liability for performance failure due to the incorrect application of our products. Correct application is critical to the successful performance of our products and as this process falls outside of our control we are unable to cover the application under our product performance warranty. Where there are doubts, it is recommended that the user conduct their own suitability tests before use.

Updated: February 2016 (this supersedes all previous publications)